

Backpack Vibrators



When concrete consolidation is required for remote or mobile applications, there's nothing like a Northrock Backpack Vibrator System. These units are designed for use where electrical power is not conveniently available or for applications where extra mobility is desired. No tangled air hoses or electrical extension cords.

Northrock Backpack Vibrators offer just the right 10,000 vpm mid-fre-

quency and force characteristics required to set material particles in motion fast for rapid consolidation of homogenous mixes without destroying important freeze-thaw pressure-relief chains produced by small air bubbles. And Northrock concrete vibrators are designed to maintain these optimum frequencies regardless of slump, head diameter or other load conditions.

Power Units

Northrock Backpack Vibrators are driven by a fuel-efficient two-cycle, 50cc, 2- $\frac{1}{2}$ hp gas engine. This power unit is lightweight yet powerful enough to drive any of Northrock's 7', 10' or 14' flexible shafts and vibrator heads up to 2" in diameter. A quick connect/disconnect system allows for assembly/disassembly in seconds.

The power unit is also designed for ease of operation and operator com-

fort. The engine swivels 260° for either right- or left-hand side operation for maximum flexibility and minimum fatigue. The engine throttle control and kill switch are placed conveniently at the side of the operator. An ergonomically designed frame with strategically positioned motor mounts isolate vibration from the operator.

Flexible Shafts

Northrock Backpack Vibrator Systems offer a choice of standard heavy-duty shafts for better pokeability and light-duty pencil shafts for better flexibility.

They are available in lengths of 7', 10' and 14'.



Special Heads – A short 4-1/2" head is available for slabs, tilt-up and other precast work. Coated heads from 1-1/2" to 2" diameter are available to protect rebar and soft tips are available to protect expensive forms.

With a wide range of poker vibrator heads and flexible shafts, Northrock Backpack Vibrator Systems offer the right combination for concrete contractors, rental houses and equipment dealers looking for a rapid return on investment. For the dealer nearest you, call Northrock directly at 1-800-989-8423.



Vibrator Heads

VIBRATOR HEAD SPECIFICATIONS

Head Diameter & Length inches / mm	Centrifugal Force pounds / N	Amplitude to side at tip inches / mm	Radius of Influence inches / mm	Capacity y3/hr / m3/hr
3/4 x 12 19 x 305	112 498	.070 1.78	4 102	4 3.64
1 x 13 25 x 330	183 820	.075 1.91	5 127	6 5.46
1-1/4 x 13 32 x 330	430 1,913	.080 2.03	7 178	8 7.28
1-1/2 x 14 38 x 356	760 3,380	.090 2.29	14 356	12 10.92
1-3/4 x 14 44 x 356	1100 4,893	.110 2.79	18 457	24 21.84
2 x 14 51 x 356	1450 6,450	.130 3.30	22 559	35 31.85

Six Northrock vibrator heads are available in a range of diameters from 3/4 inch up to 2 inches. Diameter is selected by the scope of the job and desired productivity. High levels of centrifugal force and amplitude are generated by rotating Northrock's unique eccentric weights at the desired frequency within the head. A special oil bath system keeps the weights lubricated at all times. All heads are sealed at the factory and are maintenance free.

Lifetime Warranty

All Northrock products are manufactured to the highest quality standards. If a vibrator fails due to a manufacturing defect, we will repair or replace it at absolutely no charge for the life of the product.

SPECIFICATIONS

Engine: 50cc Gasoline – 2 1/2 hp
 Flexible Shafts: 7', 10', 14'
 *Vibrator Heads: 3/4", 1", 1 1/4", 1 1/2", 1 3/4", 2"
 Vibration Frequency: 10,000 vpm

*As a rule of thumb, the head size of the backpack vibrator system should be selected to match the maximum aggregate size of the pour.

Other Northrock Products



Concrete Vibrators



Concrete Grinders



Power Screeds



Your Authorized Dealer:

3688 Horseblock Road • Medford, NY 11763
 phones: 800-989-8423 or 631-924-6130
 faxes: 800.315.1277 or 631.924.6369
 www.northrockindustries.com